Superior vinyl

Durability

Freedom from wear

Heat/cold resistance

Highest consumer satisfaction





Features

Hardware & Glass Options



The Victorian Patio Door **Performance Series** is

manufactured from the most advanced vinvl. A high-grade resin recipe unmatched for strength and freedom from wear. Offering beauty and performance - it will not rot, rust, pit or blister over long periods of time.

Our multi-chambered, allvinyl frame is durable and easy to install. Maximized strength withstands high winds and provides superior air tightness. Sunview

Patio Doors are ideal for new construction and available with the highest quality accessories and upgrades including security, colour and finishing options. Our goal - the highest buyer satisfaction.

Stays cool in summer

Stavs warm in winter

Standard Hardware

Elite handles come as the standard door hardware. Available in white, black, ivory or sandalwood.



Optional

- 1_{1/4}", 2", or 3_{3/8}" frame extensions
- Sill extensions

Frame & Sash

- 41/2" sill plate
- Brick mold

Optional Sidelites and **Transoms**

Frame your patio door in outdoor light with a transom or sidelite. The frame is made of PVC, virtually maintenance-free and available in a wide selection of finishes and glass types.

Optional Hardware

These unique handle sets can be configured with single-point or heavy duty multi-point keylocks and are available in White, Black, Brass, Black Nickel, Satin Nickel or Bright Chrome.



Optional Security Locks



Two Position Kick Locks mount on the bottom of the operating door. Used as secondary lock. Available in white, beige or brown.



Guardian Locks mount on the top of the operating door; security bolt locks into the frame. Available in white, beige or brown.



Optional V-Groove Glass Decorative and elegant.

Folding Security Bars

mount on the fixed side of the door frame and swing down to stop the door from operating.



Optional Internal Mini-Blinds

- Fingertip operation
- No external cords
- No dusting
- Low-E glass

Maximum visibility to complete privacy at the tip of a finger. The lever raises, lowers or tilts the blinds sealed between the insulated glass to ensure maintenance-free operation.



Standard Colonial: 5' and 6' door -3x5 Grid Pattern; 8' door -4x5 Grid Pattern






Optional Exterior Colours

Sunview Patio Doors boast a wide range of colour options that feature a finish which is U.V. stable, has a superior adhesion process



Optional Decorative Grills

Internal grills are available in a wide range of design styles with colours that include Flat Grills in Two-tone. White, Brass and Pewter, Georgian Grills in White, and Pencil **Grills** in White, Brass and Pewter.



Durable Sash

Vinyl Frame

• 3 weather seals

• 57/8" mechanically fastened vinyl frame • Components easily installed and replaceable

• 8 degree sill slope for optimal drainage

Anodized screen track/stainless steel roller track

• 1" sealed units for optimal thermal performance

Super Spacer®

Glazing

Enhancing the

outstanding thermal efficiency is the

1" high-performance

glazing found in

Low-E glass and


Super Spacer®

Edgetech


technology.

Specifications


Dimensions Door/Panel Configurations and Finished Sizes (Exterior view)




OX-Slide left




XO-Slide Right



OXO-Slide R to L or OZO-Slide L to R



X00-Slide R or 00X Slide L



OXXO-Slide R and Slide L from Centre

2 Panels

58 1/2 W	Х	79 1/2 H
59 _{1/2} W	Х	79 _{1/2} H
59 _{1/2} W	Х	81 _{1/2} H
59 1/2 W	Х	95 1/2 H
70 _{1/2} W	Χ	79 _{1/2} H
71 _{1/2} W	Х	79 _{1/2} H
71 1/2 W	Χ	81 1/2 H
71 _{1/2} W	Х	95 _{1/2} H
95 _{1/2} W	Χ	79 _{1/2} H
95 1/2 W	Χ	81 1/2 H
95 _{1/2} W	Χ	95 _{1/2} H

3 Panels

88 3/4 W X	79 1/2 H
88 3/4 W X	81 1/2 H
88 3/4 W X	95 1/2 H
1063/4 W x	791/2 H
1063/4 W x	8 1 1/2 H
1063/4 W x	95 _{1/2} H
1423/4 W x	79 _{1/2}
1423/4 W x	8 1 1/2 H
1423/4 W x	95 _{1/2} H

4 Panels

Х	79 _{1/2} H
х	81 _{1/2} H
Х	95 _{1/2} H
Х	79 _{1/2} H
Х	81 _{1/2} H
Х	95 _{1/2} H
Х	79 _{1/2} H
х	81 _{1/2} H
Х	95 _{1/2} H
	x x x x x

Performance Victorian Patio Door Series meets NAFS/Class LC-PG55-Type SD

Standard	Air Tightness	Water Tightness	Structural Load
AAMA/WDMA/CSA 101/1.S.2/A440-08	75 Pa-0.5 L/s.m2	400 Pa (8.35 psf)	3960 Pa (82.71 psf)
	Passed	Passed	Passed





Distributed By:



Our products meet the Energy Star program guidelines for helping businesses and individuals protect the environment through superior energy efficiency.

