High value
High quality
High performance
High efficiency
High style





Features and Specifications



Sunview Patio Doors'

value-priced series starts with the most advanced vinyl. A high-grade resin unmatched for strength and freedom from wear it will not rot, rust, pit or blister over long periods of time. Door ships



Elegant Hardware

Available in standard White and Black. Optional upgrade to Brass, Nickel, Satin Chrome or Bright Chrome.



Glazing

High-performance glazing with Low-E glass and Edgetech Super Spacer® technology.



Super Spacer

Optional Decorative Grills

Internal grills are

Optional Locks

in white, beige or brown.

all hardware handles.

Two Position Kick Locks mount

on the bottom of the operating

door. Used as secondary lock

when the door is closed. Available

Multi-point Locks provide two

heavy duty locking points on

the door frame. Available on

available in a wide range of design styles with colours that include **Flat Grills** in White: Georgian Grills in White, Brass or Pewter and Pencil Grills in White, Brass and Pewter.



Frame

- weather seals
- 47/8" welded vinyl frame
- Components easily installed and replaceable
- Stainless steel roller track


Welded Sash

- Reinforced with steel to withstand higher wind loads
- Double perimeter seal for superior air-tightness
- Doors are easily and completely reversible
- Adjustable nylon tandem ball-bearing rollers
- 1" sealed units for optimal thermal performance


Dimensions Door/Panel Configurations and Finished Sizes








OXO-Slide R to L or





2 Panels

59_{1/2} W x 79_{1/2} H 71_{1/2} W x 79_{1/2} H 95_{1/2} W x 79_{1/2} H

87_{1/2} W x 79_{1/2} H 105_{1/2} W x 79_{1/2} H 141_{1/2} W x 79_{1/2} H

3 Panels

4 Panels

116_{1/2} W x 79_{1/2} H 140_{1/2} W x 79_{1/2} H 188_{1/2} W x 79_{1/2} H

Optional Exterior Colours

A wide range of colour options feature a finish which is U.V. stable, has superior adhesion and is impact



Performance Windsor Patio Door Series meets NAFS/Class R-PG50-Type SD

Standard	Air Tightness	Water Tightness	Structural Load	Reinforcement
AAMA/WDMA/CSA 101/1.S.2/A440-08	75 Pa-0.5 L/s. m2	360 Pa (8.35 psf)	3960 Pa (82.71 psf)	IntLk Steel Reinf.
	Passed	Passed	Passed	T & B Reinf.



Standard	Air Tightness	Water Tightness	Structural Load	Reinforcement
AAMA/WDMA/CSA 101/1.S.2/A440-08	75 Pa-0.5 L/s. m2	290 Pa (8.35 psf)	3960 Pa (82.71 psf)	IntLk Steel Reinf.
	Passed	Passed	Passed	



www.sunviewdoors.com

